

I-TRAP

125 LED WP

CEILING MOUNTING SYSTEM

With its innovative design, the i-trap 125 LED WP is recommended for use in wet environments like bottling areas, breweries etc.

The unit can be ceiling mounted with 2 metal chains and offers easy



ASTRON UY

INSECT

CONTROL



Energy savings & effective fly control

go hand in hand

i-trap 125 LED WP ceiling mounting system.

With its discreet design, the i-trap 125 LED WP is recommended for use in supermarkets, warehouses, stores and dry industrial environments..

Easy to service, stylish and effective; the i-trap 125 LED WP offers it all.





LED lambs

LED technology offers clear advantages in terms of efficiency (lower energy consumption) and its lifespan (3 years).

Glueboards

Insects are caught on a glue layer, which preserves them over time. The caught insects can be counted and insect species can be analysed, which offers clear advantages in an IPM approach.

10 reasons to start using the i-trap 125 LED WP:

- Effective & proven design
- Energy saving UV-A LED technology offers over 276 kW of savings per unit per year.
- Lifespan of 3 years (25.000 hrs) with this UV-A LED lamps which means significantly less landfill when compared to fluorescent lamps that are replaced annually.
- Environmentally friendly: no restricted chemicals used in the product design.
- RoHS / REACH / ISO and CB compliant
- Fast and simple maintenance of the unit.
- Optimized glueboard offers fast catch results and a fast analysis
- High quality casing
- Fast mounting and fast service

Guarantee: 2 years on electrical failures

Technical specifications

Area coverage : 125 m²

Light source : 4x 9 Watt ASTRON UV-A LED lamps

Type of UV lamps : UV LED Lamps RoHS certified

Electrical supply : $100-240 \text{ V} \sim 50-60 \text{ Hz}$

Catch specifications : By means of long life glueboard

Power consumption : 36 W Weight : 6 kg Degree of protection : IP65

Guarantee : 2 year return to base

Int. building norm : acc. IEC-335-259 int. standard for insect exterminators

 $\begin{array}{lll} Lamp \ life \ time & : & 25.000 \ hrs \ (*) \\ Dimensions \ (L \times D \times H) & : & 500 \times 170 \times 360 \ mm \end{array}$


CE-approval : Yes


Mounting position : Ceiling mounted
Cable/Chains : Included 2x 1.3 m

Packaging : Transport box with b/w print
Manual : Enclosed with the unit in English

Service : Unit can be dismantled without special tools

(*) after 25.000 hours a loss of 30% in efficiency has to be expected and lamps need to be replaced





2024-07